

Ultralift™ 3510XH Mobile Patient Electric Lift

The industry standard for safe and comfortable patient lifts.

The Ultralift™ 3510XH features a standard power base widening system allowing caregivers to perform all functions with the push of a button and no strain. The Ultralift™ 3510XH is also equipped with Tollos' new proprietary iQ Technology™, providing intuitive diagnostics for smarter lifting. iQ uses a digital readout that tracks critical lift data to ensure caregiver compliance, and displays important service and maintenance data, including service alerts at 1000 cycles, to maximize useful life of the lift.

Lift patients of up to 600lbs (750 lb model also available), rotate a patient for an unobstructed 360 degrees, accomplish 'head first' floor lifts, and more with the Ultralift™ 3510XH.

The new Ultralift™ 3510XH features the highest lifting range in the industry. The boom raises up to 90.5" for maximum lifting height, while the spreader bar extends as low as 12" from the ground to easily accommodate patients on the floor. With optional integrated scale, the lifting height increases by an additional six inches, while reducing cost by a third or more.

Our true six-point spreader bar, paired with versatile repositioning slings, make this equipment extremely multi-purpose in the tasks with which it can assist, including repositioning, rehabilitation, limb fitting, and turning.



The new Ultralift™ 3510XH features the highest lifting range in the industry. The boom raises up to 90.5" for maximum lifting height, while the spreader bar extends as low as 12" from the ground to easily accommodate patients on the floor.



An ergonomic control panel with a dual battery warning system, dual controls and optional integrated scale (shown) means the Ultralift™ 3510XH is always charged and ready to use.



The true six-point spreader bar with spring-loaded locking clips, paired with versatile repositioning slings, make this equipment extremely multi-purpose in the tasks with which it can assist, including repositioning, rehabilitation, limb fitting, and turning.



Lift patients of up to 600lbs (750 lb model also available), rotate a patient for an unobstructed 360 degrees, accomplish 'head first' floor lifts, and more with the Ultralift™ 3510XH.

Ultralift™ 3510XH Mobile Patient Electric Lift

Ultralift™ 3510XH Mobile Patient Electric Lift

- The Ultralift™ 3510XH is the latest version of the industry's safer, most user-friendly mobile electric patient lift ever.
- Manufactured in North America, the 3510XH includes a long list of standard features specifically engineered to optimize patient comfort and safety as well as reduce caregiver injury.
- This piece of equipment is ideally used for effective gait training and general rehabilitation activities.
- Optional low profile base option (2.5" casters) allows lift to clear under even the lowest of low beds or stretchers.

iQ Technology™

Lifting and transferring has never been more intuitive with the integration of iQ Technology™. By utilizing proprietary electronics, mated to a digital readout and optional integrated scale, caregivers and maintenance can now track critical lift and service data simply with the push of a button. Data displayed includes total lifts, total hours, total battery charges, current battery level, total low battery warnings, last/next service plus visual alerts every 1,000 cycles for preventative maintenance, and an automatic shutdown at 6000 lift cycles.

Optional Integrated Scale

- Optional integrated scale saves up to 8 inches of lighting height and 40% cost versus external scale
- Eliminates maintenance including replacing batteries on external scale

Features

- 600 lb lifting capacity (750 lb version also available)
- iQ Technology™
- Power base widening
- Extra long boom
- Heavy duty castors
- Flat base option (2"-2.5")
- Integrated scale option
- True six-point spreader bar
- Extended lifting range of 65 inches
- 5 year warranty of frame, 3 year on actuator, 1 year on electronics
- 3500B base model option

TECHNICAL SPECIFICATIONS

Operation:	Electric Actuator
Front Castors:	100mm or 4" (optional 3" low clearance) (also optional flat base)
Rear Castors:	125mm or 5" (optional 4" low clearance)
Power Source:	Two 12V, 2.6Ah batteries
Charger:	24VCSA/UL approved
Overall Weight:	53kg or 117lb
Height (top of mast):	1325mm or 52"
Construction:	Rectangular Steel Tubing
Spreader Bar (Highest):	2121mm or 83.5"
Spreader Bar (Lowest):	305mm or 12"
Finish:	Polyester powder coat, baked
Emergency Stop Switch:	Standard
Overall Length:	1219mm or 48"
Emergency Up/Down Switch:	Standard
Digital Weigh Scale:	Optional
Base Width - Closed:	629mm or 24 1/4"
Removable Battery Pack:	Optional (Model TUL3500XHP)
Wishbone Style Spreader Bar:	Optional
Approved Lift:	CSA-Z10535-03
Charger:	CSA/UL

Ultralift 3500 Base Model



Optional flat legs



Optional Steering Castor



Optional External Scale

