

# SWASH BL67

ADVANCED BIDET SEAT

**brondell**<sup>®</sup>  
a healthy home experience



**BL76-EW / BL67-RW**

*Elongated White / Round White*

Discover a whole new level of better bathroom hygiene with Swash BL67 and the complete feature set of an advanced bidet seat. Comes with all parts for a standard installation, including a 7/8 inch metal T-valve and a 25 inch metal braided bidet hose with 1/2 inch connectors.

## TECHNICAL SPECIFICATIONS

<b>Model / SKU</b>	BL67-EW / BL67-RW
<b>Power Voltage</b>	120V / 60Hz
<b>Max Power Consumption</b>	870W
<b>Supply Water Pressure</b>	9.95 psi – 106.7 psi
<b>Dimensions</b>	<b>Elongated:</b> 18.5 in x 20.7 in x 5.7 in / <b>Round:</b> 18.5 in x 19.5 in x 5.7 in
<b>Power Cord Length</b>	3.9 ft
<b>Weight</b>	<b>Elongated:</b> 11.24 lbs / <b>Round:</b> 10.8 lbs
<b>Incoming Water Temperature</b>	37.4°F – 104°F
<b>Seat Weight Limit</b>	330 lbs
<b>Lid Weight Limit</b>	160 lbs
<b>Seat Opening Dimensions</b>	<b>Elongated:</b> 11.9 in x 8.1 in / <b>Round:</b> 10.6 in x 8.1 in
<b>Mesh Filter</b>	0.51 in x 0.44 in diameter



**1 YEAR** STANDARD WARRANTY

# SWASH BL67

ADVANCED BIDET SEAT

**brondell**<sup>®</sup>  
a healthy home experience

## HEATED SEAT SPECIFICATIONS

<b>Seat Temperature Control</b>	<b>4 levels:</b> Off – room temperature, Low – 93.2°F, Medium – 100.4°F, High – 107.6°F
<b>Max Heater Power Consumption</b>	55W
<b>Safety Devices</b>	Thermostat, Thermal Fuse, Thermal Sensor, Seat Occupied Sensor

## WARM WATER WASHING DEVICE

<b>Rear Wash</b>	Maximum 0.8 L/min., automatic nozzle self-cleaning
<b>Front Wash</b>	Maximum 0.8 L/min., automatic nozzle self-cleaning
<b>Strong Wash</b>	Maximum 0.6 L/min., automatic nozzle self-cleaning
<b>Standard Time</b>	<b>Rear Wash:</b> 2 minutes / <b>Front Wash:</b> 2 minutes / <b>Strong Wash:</b> 2 minutes
<b>Water Pressure Control</b>	5 levels
<b>Water Temperature Control</b>	<b>4 levels:</b> Off – incoming water temp., Low – 91.4°F, Medium – 96.8°F, High – 102.2°F
<b>Max Heater Power Consumption</b>	800W
<b>Safety Devices</b>	Thermal Fuse, Thermostat, Water Level Sensor, Thermal Sensor, Bi-metal

### HYGIENE

- Rear, Front, and Strong wash
- Stainless-steel nozzle
- Positionable nozzle
- Adjustable water pressure
- Adjustable water temperature
- Nozzle oscillation

### COMFORT


- Gentle Wash function
- Ergonomic heated seat with adjustable temperature
- Massage and pulse
- Continuous heated water

### CONVENIENCE

- Illuminating nightlight
- Dual Eco Mode for energy savings
- Sidearm control panel
- Gentle-closing seat and lid
- Quick release seat

### REQUIRED MEASUREMENTS

- A. Center of bolt holes to front of toilet bowl**  
Elongated Swash models: 18"–19.5"  
Round Swash models: 16"–17.75"
- B. Distance from center of bolt holes to toilet seat tank**  
All models: Minimum 1.5"
- C. Distance between bolt holes**  
All models: 5.25"–7.45"



**1 YEAR** STANDARD WARRANTY