## **BLUE SPRING BATHING SYSTEM**

The Blue Springs Bathing System is designed to be installed in a standard bathtub or shower alcove for a more residential appearance. The low threshold side-entry door allows easy access for both ambulatory residents and those who need assistance. The easy to use wall-mounted modular control panel can be positioned for convenient operation by either the resident or caregiver. The Blue Springs Bathing System will give the bathing area an upscale look and create the atmosphere of a luxury spa.

DB-BLUE-1000With Modular ConsoleDB-BLUE-1100Disinfectant System and Modular ConsoleDB-BLUE-1200Disinfectant System, Air Spa and Modular Console

## 400 lb. WEIGHT CAPACITY

## FEATURES:

- Thermostatic mixing valve Provides an anti-scald protection that dispenses 15 gallons per minute for fast tub fill.
- Built-in disinfection system The most time-efficient solution for disinfection of the bath's external surfaces and minimizes the risk of cross-infection. The built-in disinfection system cabinet is conveniently located on the top side of the tub for easy access. The lockable cabinet provides a secure place for cleaning supplies and disinfectants.
- Handheld shower wand Hair and upper body washing can be used at the same time the tub is filling.
- Water temperature display Monitors tub-fill and shower wand temperatures.
- 3/4" supply lines Constructed of stainless steel mesh clad.
- Lap and shoulder harness Used for resident safety.
- Secondary door lock Prevents accidental door opening when in use.
- The CleanDrive Air Spa System Variable speeds and pulse modes designed to enhance the bathing experience for the resident and caregiver.

## Additional features of the CleanDrive Air System include:

- The hydro massage provides millions of preheated air bubbles in the water which increases stimulation of peripheral blood circulation, reduces pain and inflammation in the joints, gently massages away dirt, and induces deeper relaxation.
- The CleanDrive Air Spa System is a hygienic and low maintenance hydro massage system featuring 12 air jets with spring loaded check values for back flow prevention. It prevents water from entering the air lines, eliminating the extra step to disinfect air lines. The CleanDrive Air Spa System simplifies disinfection and reduces the possibility of cross-contamination.
- Unlike most other whirlpool and air spa systems, the CleanDrive Air Spa System does not allow water to enter the air lines to reduce the growth of bacteria and mold.
- The motor is quiet, efficient, and has a ceramic heating element that blows warm air to help maintain the water temperature and warm the surface of the tub.
- Warranty: 5 Years on finishes and composite shell, 3 years on all moving and stationary parts, and lifetime on the door seal.







The Modular Control Panel includes the tub-fill and shower valves, water temperature display, thermostatic mixing valve, and CleanDrive Air Spa System control pad.



The Blue Spring is designed to enhance the bathing experience for the resident and create the atmosphere of a luxury spa.

Made



The built-in disinfection system cabinet is conveniently located on the top of the tub for easy access. The lockable cabinet provides a secure place for cleaning supplies and disinfectants.

|                             | in the<br>USA         |
|-----------------------------|-----------------------|
| SPECIFICATIONS              |                       |
| Width:                      | 32"                   |
| Length:                     | 59.75"                |
| Height:                     | 38"                   |
| Seat Height:                | 21" (from floor)      |
| Seat Width:                 | 21"                   |
| Threshold Height:           | 13"                   |
| Transfer Device Access:     | 6" H x 41" W          |
| Water Supply Inlet:         | 3/4" diameter         |
| Drain Size:                 | 1.5"                  |
| Water Capacity (Occupied):  | 48 gallons            |
| Fill Time:                  | 3 minutes, 12 seconds |
| Drain Time:                 | 1 minute, 58 seconds  |
| Weight Capacity (resident): | 400 lbs               |
| Door Configuration:         | Right or Left Hinge   |
| Electrical Supply:          | 115V AC; 60Hz; 15 amp |