

Blue Spring Bathing System



HCPCS:



FIGURE A



FIGURE B




FIGURE C



FIGURE D

- Thermostatic mixing valve - Provides an anti-scald protection that dispenses 15 gallons per minute for fast tub fill
- Built-in disinfection system - The most time-efficient solution for disinfection of the baths external surfaces and minimizes the risk of cross-infection
- The built-in disinfection system cabinet is conveniently located on the top side of the tub for easy access
- The lockable cabinet provides a secure place for cleaning supplies and disinfectants
- Handheld shower wand - Hair and upper body washing can be used at the same time the tub is filling
- Water temperature display - Monitors tub-fill and shower wand temperatures
- 3/4" supply lines - Constructed of stainless steel mesh clad
- Lap and shoulder harness - Used for resident safety
- Secondary door lock - Prevents accidental door opening when in use
- The CleanDrive Air Spa System - Variable speeds and pulse modes designed to enhance the bathing experience for the resident and caregiver

PRODUCTS

PRODUCTS	Description
DB-BLUE-1000	Side Access 60in
DB-BLUE-1100	Side Access 60in on board Disinfect
DB-BLUE-1200	Side Access 60in on board Disinfect

SPECIFICATIONS

SPECIFICATIONS	Description
Dimensions	32" (W) x 59.75" (L) x 38" (H)
Door Configuration	Right or Left Hinge
Drain Size	1.5"
Drain Time	1 Minute, 58 Seconds
Electrical Supply	115V AC, 60HZ, 15 amp
Fill Time	3 Minutes, 12 Seconds
Seat Dimensions	21" (W) x 38" (H)
Threshold Height	13"
Transfer Device Access	6" (W) x 41" (H)
Water Capacity (Occupied)	48 Gallons
Water Supply Inlet	3/4" Diameter
Weight Capacity	400 lbs