

BAILEY

STANDARD FABRIC COLOR SELECTOR - SOFT VINYL



NOTE:

These colors are provided as a guideline and will vary for every printer and monitor.
If color matching is required please request a sample swatch before ordering!

HERCULITE COLORS - REINFORCED VINYL



NOTE:

Herculite material and colors are subject to availability and may change or become unavailable at any time.
Check for current stock before ordering if Herculite is a requirement for your Mat or Mat Table!

BAILEY MANUFACTURING COMPANY
118 LEE STREET
PO BOX 130
LODI, OH 44254

BAILEY

NASSIMI



ESPRIT colors are part of the Team Performance line of premium vinyl fabrics. They are manufactured to meet the following standards:

PERFORMANCE SPECIFICATIONS

Abrasion Resistance: 100,000+ Double Rubs per ASTM D 4157-92 Wyzenbeek / CFFA-1A
Mildew Resistant: ASTM G21-96 / CFFA-120
Anti Bacterial: AATCC 147 / CFFA300
Anti Microbial: ASTM G21 / CFFA 120
Ultra Violet Resistant: 1000 Hours ASTM G26-96 Method C / CFFA-2
Cold Crack: -20° F Federal Standard No. 191A-Method 5874 / CFFA-6
Stain Resistant: ResilienceSR Protection
Sulfide Stain Resistant

FLAMMABILITY* REQUIREMENTS

California Fire Code
Technical Bulletin No. 117, Section E
BIFMA
UFAC Class 1
MVSS 302
NFPA 260
IMO A.652 (16) 8.2
IMO A.652 (16) 8.3
May Comply with California 133 when Tested with Suitable Components
Can be Treated to Pass FAA 25.853

Resilience SR represents the latest Vinyl Protection:

Stain Resistance: With proper care, vinyl can be easily cleaned and will guard against stains.

Anti-Microbial & Anti-Bacterial Protection: Inhibits bacterial growth, as well as fungus, mold and mildew spores.

Abrasion Resistance: Provides additional wear properties and surface durability, increasing the life of the material.

Resilience SR is not visible, and does not affect the feel of the material. Resilience SR will resist repeated cleaning and wear.

Resilience SR complies with ASTM G 21 / CFFA 120 and AATCC 147 / CFFA 300 and inhibits the growth of the following:

Aspergillus Niger Staphylococcus Aureus Penicillium Pinophilum Klebsiella Pneumoniae
Chaetomium Globosum Salmonella Choleraesuis Trichoderma Virens Pseudomonas Aeruginosa
Aureobasidium Pullulans

The information in this guide refers to performance of Resilience in tests conducted under laboratory conditions. This information does not imply a specific guarantee and does not relieve the user from the responsibility of the proper and safe use of the product and referenced cleaning agents.

HERCULITE®

Brand Fabric

#20 and #80 laminated and reinforced fabrics are manufactured to Military Specifications to be Abrasion resistant, Mildew/Rot Resistant and Flame Retardant* per the following standards and testing methods:

Quality Standard MIL-C-43006

Federal Fire Standard 191-5903

*The terms Flammability, Fire Retardant and any corresponding data refer to typical performance in the specific tests indicated, and should not be construed to imply the behavior of this or any other material under actual fire conditions.

BAILEY MANUFACTURING COMPANY
118 LEE STREET
PO BOX 130
LODI, OH 44254