

# CPP

## Portable Motor



The light weight, 10lbs., Robust CCP has a 440 lbs. weight capacity, backed by a solid 5-year warranty. Its intuitive design and cutting-edge electronics place it at the top of its class.



### **Unique Hanger Bar Design**

#### **Clearance**

The hanger bar is positioned beneath the lift, providing increased clearance between users and the lift.

#### **Quick Release**

The hanger bar features a convenient quick-release mechanism for easy movement and storage.

#### **Swivel Connection**

The hanger bar is designed to swivel in the direction of the pull, not the lift, preventing any binding of the lifting strap.



#### **Dual Controls**

Up, down, and emergency lowering functions are available on both the handset and lift unit.



#### **Superior Charging System**

High battery capacity supporting 50-60 lifts per charge with a auto power-off after approximately 30 seconds of non-use.

# CPP

## Specification

<b>Max Safe Working Load:</b>	440 lbs (200 kg)
<b>Hoist Case:</b>	Non Flammable ABS Plastic
<b>Total Weight (Unboxed):</b>	9.9 lbs (4.5 kg)
<b>Dimensions (L / W / H)</b>	8.19" / 6.97" / 5.87"
<b>Rail Transfer:</b>	Manual
<b>Lifting Range:</b>	Up to 82.68" (2100 mm)
<b>Lifting Speed (Unloaded):</b>	1.38 "/s (35 mm/s)
<b>Lifting Speed (Loaded):</b>	0.98 "/s (25 mm/s)
<b>Charger Input:</b>	100-240 V
<b>Charger Output:</b>	24 V – 1.33 A
<b>Emergency Lower:</b>	Electric
<b>Hand Control:</b>	Wired Electric 3 Button
<b>In Track Charging:</b>	Not Available
<b>Removable from Track:</b>	Yes
<b>Duty Cycle:</b>	15% use, 85% rest
<b>Batteries:</b>	2 x 12 V – 3.3 Ah (NiMH)



Slide Tubes

