

COMFORTWIDE™ SERIES

Low Bed Frames



COMFORT WIDE™

Push-button slide technology with locking positions 35-39-42 inches wide



EVAC POSITION™

Pass through doors no matter the assist device attached

EX6000 MODEL

Evac Position™ – extra position to make the bed thinner so if a side bar is attached it can still pass through doors less than 42 inches wide

No Tools – the bed can be assembled and un-assembled without the need of tools

Comfort Wide™ – bed expands to 42 inches wide without the use of tools for more comfort and flexibility

Easy Storage and Transport – the bed can be un-assembled in minutes and transported in tight areas

Wall Bumpers – soft non-marking bumpers come standard to protect wall from damage

Steel Pivots – each pivot has hardened steel bushings or high bolts to extend the life of the bed

Positions - trendelenburg/reverse trendelenburg and cardiac chair can be quickly achieved with the 5 function handset

PHYSICAL SPECIFICATIONS

Deck Height Low.....	9"
Deck Height High.....	25"
Sleeping Surface.....	35"w, 39"w, 42"w x 80"l
Maximum Safe Working Capacity.....	600 lbs
Product Weight	
Foot Section Lift.....	42 lbs
Head Section Lift.....	42 lbs
Head Section Sleep Surface.....	80 lbs
Foot Section Sleep Surface.....	80 lbs
Maximum Back Angle.....	65°
Maximum Knee Angle.....	23°
Mobility Height.....	any height

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature.....	41° F to 104° F (5° C to 40° C)
Operating Relative Humidity.....	20% to 90% @ 86° F / 30° C
Operating Atmospheric Pressure.....	700 to 1600 hPa
Storage Temperature.....	-10° C to -50° C
Storage Relative Humidity.....	20% to 90% @ 86° F / 30° C
Storage Atmospheric Pressure.....	700 to 1060 hPa

ELECTRICAL SPECIFICATIONS

Main Voltage Input.....	120 V AC
Max Current Input.....	2.70 A
Main Frequency Input.....	60 Hz
Controller Output Voltage.....	24 V

COMFORTWIDE™ SERIES




LIMITED WARRANTY

15 years on bed frame mechanics
5 years on drive system
1 year on wood, casters & handsets
Lifetime warranty on all welds

Approvals: IEC60601-1:2005 2nd edition, ANSI / AAMI ES60601-1:2005 2nd edition, and CAN / CSA-22.2 No 60601-1:2008

ENDBOARD OPTIONS



ENGLISH OAK



MAHOGANY



CHERRY



LIGHT OAK

*Custom boards are available

ACCESSORIES



4" Bed Extender



Electronic Scale



Accessory Hanger



Storage Cart



Transport Dolly



1/4 Length Side Rail



Pivoting Assist Bars



Trapeze Assembly