

The Hoyer® Calibre® is a uniquely designed electronically operated patient lift for the safe lifting of heavier patients. It is both sturdy and robust with a safe working load rating of 850 lbs. The Calibre has been designed to be configured with a weigh scale included. The weigh scale is seamlessly integrated with a digital display on both sides and user-friendly controls.



Smart Monitor

The unique Smart Monitor control box is programmable and will accurately record and display vital lift utilization and service data. An easy to read LCD display provides the valuable information at the touch of a button.



6-Point Cradle

The large, open cradle results in less discomfort to the patient caused by pinching and squeezing.



Powered Base

The powered base allows the legs to be opened and closed to enable access around armchairs, wheelchairs and similar obstacles without bending or twisting.



Standard Scale

The scale allows the caregiver to adjust the position of the display for easier viewing. Simple, intuitive controls provide the resident's weight in pounds or kilograms.

SPECIFICATION

	IMPERIAL	METRIC
Safe Working Load	850 lbs	386kg
Maximum Overall Length	64"	1626mm
Reach at Maximum Height	28"	711mm
Reach at Minimum Height	26"	660mm
Maximum Reach*	37"	940mm
Legs Open - External Width	55.25"	1403mm
Legs Open - Internal Width	49"	1245mm
Legs Closed - External Width	33.25"	845mm
Legs Closed - Internal Width	26.75"	679mm
Overall Height of Legs	4.75"	120mm
Ground Clearance	1.2"	30mm
Front Twin Casters	4"	102mm
Rear Braked Casters	4"	102mm

*Reach = Center of spreader bar to the front of the mast

WEIGHTS

	IMPERIAL	METRIC
Mast, Base, Boom Assembly, Cradle	240 lbs.	109kg
Power Pack	6.6 lbs.	3kg
Total	246.6 lbs.	112kg
6-Point Spreader Bar	20 lbs	9kg

All measurements are within a +5/-5% tolerance.

6-POINT SPREADER BAR (MEASUREMENT TO TOP OF LOCATION PINS)

Cradle Maximum Height	77"	1956mm
Cradle Minimum Height	30"	762mm

ELECTRIC SHOCK PROTECTION

Charger – Class II
Lift – Internal power source

DEGREE OF SHOCK PROTECTION

Charger – Type B
Lift – Type B
Intended operating environment: >+5°C <+40°C
Outside this environment, functionality and safety may be compromised

ELECTRICAL SPECIFICATIONS

Batteries – 2x12 volt Rechargeable sealed lead acid type
Battery Capacity – 3.2 Ampere Hours
Charger Rated Input – 100/240VAC 50/60Hz
Charger Rated Output – 27.4/29 VDC@0.8A