



MARAMEC SPRING BATHING SYSTEM

The Maramec Springs Bathing System designed specifically for care facilities that need to bathe residents of size. The low threshold side-entry door allows easy access for larger residents with various degrees of mobility. The extra-wide built-in contoured seat allows the larger resident to sit comfortably and safely in a slightly reclined position. The Maramec Springs Bathing System is designed to be installed against a wall, allowing the caregiver access to the resident from 3 sides. Caregivers will enjoy the Maramec Springs Bathing System for its ease of use and the improved quality of care they can provide their larger residents. The Maramec Springs Bathing System has smooth and soft lines that will enhance the look of the bathing area and allow for easy maintenance and cleaning. The extra-wide contoured seat is designed to allow residents of size the opportunity to bathe in comfort.

**600 lb.
WEIGHT CAPACITY**

DB-MARAMEC-1000	Bariatric Side-Entry with Thermostatic Mixing Valve
DB-MARAMEC-1100	Bariatric Side-Entry with Thermostatic Mixing Valve and Disinfectant System
DB-MARAMEC-1200	Bariatric Side-Entry with Thermostatic Mixing Valve, Disinfectant System, and Air Spa

FEATURES:

- ◆ **Thermostatic mixing valve** - Provides an anti-scald protection that dispenses 15 gallons per minute for fast tub fill.
- ◆ **Built-in disinfection system** - The most time-efficient solution for disinfection of the bath's external surfaces and minimizes the risk of cross-infection. The built-in disinfection system cabinet is conveniently located on the top of the tub for easy access. The lockable cabinet provides a secure place for cleaning supplies and disinfectants.
- ◆ **Handheld shower wand** - Hair and upper body washing can be used at the same time the tub is filling.
- ◆ **Water temperature display** - Monitors tub-fill and shower wand temperatures.
- ◆ **3/4" supply lines** - Constructed of stainless steel mesh clad.
- ◆ **Lap and shoulder harness** - Used for resident safety.
- ◆ **Secondary door lock** - Prevent accidental door opening when in use.
- ◆ **The CleanDrive Air Spa System** - Variable speeds and pulse modes designed to enhance the bathing experience for the resident and caregiver.

Additional features of the CleanDrive Air System include:

- ◆ The hydro massage provides millions of preheated air bubbles in the water which increases stimulation of peripheral blood circulation, reduces pain and inflammation in the joints, gently massages away dirt, and induces deeper relaxation.
- ◆ The CleanDrive Air Spa System is a hygienic and low maintenance hydro massage system featuring 12 air jets with spring loaded check valves for back flow prevention. It prevents water from entering the air lines eliminating the extra step to disinfect air lines. The CleanDrive Air Spa System simplifies disinfection and reduces the possibility of cross-contamination.
- ◆ Unlike most other whirlpool and air spa systems, the CleanDrive Air Spa System does not allow water to enter the air lines to reduce the growth of bacteria and mold.
- ◆ The motor is quiet, efficient, and has a ceramic heating element that blows warm air to help maintain the water temperature and warm the surface of the tub.
- ◆ Warranty: 5 Years on finishes and composite shell, 3 years on all moving and stationary parts and lifetime on the door seal.



The Maramec Spring features an easy-to-use control panel which includes: the tub-fill and shower valves, water temperature display, thermostatic mixing valve, and CleanDrive Air Spa System control pad.



The built-in disinfection system cabinet is conveniently located on the top of the control panel for easy access. The lockable cabinet provides a secure place for cleaning supplies and disinfectants.

Made
in the
USA

SPECIFICATIONS

Width:	33.5"
Length:	60"
Height (to top of door):	36.5"
Height (to top of console):	50"
Seat Height:	21" (from floor)
Seat Width:	28"
Threshold Height:	13"
Transfer Device Access:	7" H x 41" W
Water Supply Inlet:	3/4" diameter
Drain Size:	1.5"
Water Capacity (Occupied):	52 gallons
Fill Time:	3 minutes, 28 seconds
Drain Time:	2 minutes, 10 seconds
Weight Capacity (resident):	600 lbs
Door Configuration:	Right or Left Hinge
Electrical Supply:	115V AC; 60Hz; 15 amp