

Maramec Spring Bathing System



HCPCS:



FIGURE A



FIGURE B

- Thermostatic mixing valve - Provides an anti-scald protection that dispenses 15 gallons per minute for fast tub fill
- Built-in disinfection system - The most time-efficient solution for disinfection of the baths external surfaces and minimizes the risk of cross-infection
- The built-in disinfection system cabinet is conveniently located on the top of the tub for easy access
- The lockable cabinet provides a secure place for cleaning supplies and disinfectants
- Handheld shower wand - Hair and upper body washing can be used at the same time the tub is filling
- Water temperature display - Monitors tub-fill and shower wand temperatures
- 3/4" supply lines - Constructed of stainless steel mesh clad
- Lap and shoulder harness - Used for resident safety
- Secondary door lock - Prevent accidental door opening when in use
- The CleanDrive Air Spa System - Variable speeds and pulse modes designed to enhance the bathing experience for the resident and caregiver

PRODUCTS

Description

DB-MARAMEC-1000	Baratic Side Entry w Disinfect & Thermo
DB-MARAMEC-1100	Baratic Side Entry w Disinfect & Thermo
DB-MARAMEC-1200	Baratic Side Entry w Disinfect,Thermo V

SPECIFICATIONS

Description

Dimensions	33.5" (W) x 60" (L) x 36.5" (H)
Drain Size	1.5"
Drain Time	2 Minute, 10 Seconds
Electrical Supply	115V AC, 60Hz, 15 amp
Fill Time	3 Minutes, 28 Seconds
Height	50"
Seat Dimensions	13" (W) x 28" (H)
Threshold Height	13"
Transfer Device Access	41" (W) x 7" (H)
Water Capacity (Occupied)	52 Gallons
Water Supply Inlet	3/4" Diameter
Weight Capacity (Resident)	600 lbs