

# COMFORTWIDE™ SERIES

Low  
Bed Frames



## COMFORT WIDE™

Push-button slide technology with locking positions 35-39-42 inches wide



## EVAC POSITION™

Pass through doors no matter the assist device attached

## RETRACTABED® EX5000 MODEL

**Clinical-Contour®** – exclusive feature that reduces skin shear and the repositioning of residents

**Evac Position™** - extra position to make the bed thinner so if a side bar is attached it can still pass through doors less than 42 inches wide

**Comfort Wide™** – bed expands to 42 inches wide without the use of tools for more comfort and flexibility

**Staff Lockout Control** – standard feature to prevent unnecessary operation

**Wall Bumpers** - soft non-marking bumpers come standard to protect wall from damage

**Retracting Bed Frame** – reduces potential falls and increases staff productivity

**Embedded Bed Controls** – optional fixed controls in assist bar or head rail reduces replacement handsets and increases staff productivity

**Steel Pivots** - each pivot has hardened steel bushings or high bolts to extend the life of the bed



THE INNOVATIVE HEALTHCARE SOLUTION  
www.med-mizer.com | 877-867-7365  
Made in the U.S.A.

## PHYSICAL SPECIFICATIONS

Deck Height Low.....	9"
Deck Height High.....	25"
Sleeping Surface.....	35"w, 39"w, 42"w x 80" l
Length Retracted.....	71"
Length Extended.....	85"
Maximum Safe Working Capacity.....	500 lbs
Product Weight.....	225 lbs
Maximum Back Angle.....	62°
Maximum Knee Angle.....	22°
Mobility Height.....	any height

# COMFORTWIDE™ SERIES



Fall Risk  
Non-Retractable Bed

Fall Prevention  
Retractable Bed

## ENVIRONMENTAL SPECIFICATIONS

Operating Temperature.....	41° F to 104° F (5° C to 40° C)
Operating Relative Humidity.....	20% to 90% @ 86° F / 30° C
Operating Atmospheric Pressure.....	700 to 1600 hPa
Storage Temperature.....	-10° C to -50° C
Storage Relative Humidity.....	20% to 90% @ 86° F / 30° C
Storage Atmospheric Pressure.....	700 to 1060 hPa

## ELECTRICAL SPECIFICATIONS


Main Voltage Input.....	120 V AC
Max Current Input.....	2.70 A
Main Frequency Input.....	60 Hz
Controller Output Voltage.....	24 V DC

### LIMITED WARRANTY

15 years on bed frame mechanics  
5 years on drive system  
1 year on wood, casters & handsets  
Lifetime warranty on all welds

Approvals: IEC60601-1:2005 2nd edition, ANSI / AAMI ES60601-1:2005 2nd edition, and CAN / CSA-22.2 No 60601-1:2008

### ENDBOARD OPTIONS



ENGLISH OAK



MAHOGANY



CHERRY



LIGHT OAK

### ACCESSORIES



4" Bed Extender



Pivoting Assist Bars



Battery Backup



Floor Bumper Guard



Pivoting Assist Bars with  
Fixed Handset



Trapeze Assembly



Transport Dolly



1/4 Length Side Rail  
with or without Fixed Handset



THE INNOVATIVE HEALTHCARE SOLUTION  
www.med-mizer.com | 877-867-7365  
Made in the U.S.A.