

## **21 inch 1.3 ATA** Portable Hyperbaric Chamber



Source



# Solace<sup>210</sup>

The most popular model in our Mild Hyperbaric Chamber line, the Solace 210 has a new look and added perks. With newly refined valve ports that raise the caliber of durability and safety, the upgraded sleek style of the Solace 210 combines function and elegance. All neccessary accesories are standard - frame, mattress and a set of bolsters. Priced to be practical and designed to last, the Solace 210 responds to our fundamental goal - 'Making Hyperbarics Come to You'.

#### Main Body (bladder)

4psi (1.3ATA) operating pressure

Durable double-sided 44oz. urethane coated polyester weave material

Light & portable - folds for transport in its own carry bag

Dual air-exchange/ regulator valves provide redundant pressure control

Patented 2-zipper seal facilitates self treatments

Extra large patient viewing windows

Larger external pass-through port




Inflation/Deflation valve allows both occupant and treatment administrator to control pressure



Dual redundant, air exchange valves maintain pressure and flush CO<sub>2</sub> out of the chamber

0

e210



#### **Occupant Observation**

Three windows incorporated into urethane shell

Room light illuminates chamber interior

Direct audible communication with patient

### Accessories

Chamber carry bag

Bolster set to cradle the chamber. Fabric-covered foam construction matches chamber jacket.

Chamber frame maintains form when deflated for ease of use and reduced inflation time

Mattress contoured to fit inside the chamber. Medical grade.



#### **Peripheral Equipment**

10ft. medical grade hose with quick-disconnect couplings

Analog pressure gauge

High efficiency inline air filtration. Filters air to 0.01 microns!

Double head oil-less 1/4 hp compressors with dual air intake filters





Weights	LBS	KG
Bladder Compressor Bolsters Mattress Frame	27.0 27.5 11.5 11.0 18.0	12.2 12.4 5.4 5.2 8.2
Dimensions Chamber Inflated	Inches	Meters
	Inches 92.0 22.0 70.0	Meters 2.33 0.56 1.80