

Quickstart Guide

Please read instructions/manual before installation.



UV Exposure Possible
Electrical Shock possible
If used improperly

1. Remove the PearlAqua Deca from its packaging; ensure contents of the package are complete.
2. Do not power the PearlAqua Deca without water connected to the unit
3. Installation by plumbing professional recommended
4. For installation, consider ease of access, maximum length and minimum bend radii of piping, electrical connections, and air circulation when selecting the installation location.
5. Check for water leaks after installation and before connecting to electrical supply.
6. Use appropriate connection fittings compatible with the plumbing pipework and Deca inlet/outlet ports.
7. Please refer to product manual for more details on the included USB drive.
8. Exerting excessive torque on the inlet/outlet of the Deca during installation may cause damage to internal parts. For this reason, a wrench/spanner should be used to brace the Deca during installation to reduce torque.

To ensure proper treatment do not exceed:

Input power	110 - 240V AC (24V DC power supply included)
Max. Oper. Pressure	8.3 Bar (120 psi)
Max. Water Temp.	30°C (86°F)
Max. Flow Rate	12 GPM (45 LPM)

Typical PearlAqua Deca Installation Diagram



1. PearlAqua Deca
2. Prefilter (recommended)
3. Electrical outlet
4. Water softener (where installed)

Manual for PearlAqua Deca
included on USB drive