



Utilizes small, state of the art UV-C LEDs to provide over 99.99% pathogen reduction¹ without the use of harmful chemicals or mercury-based UV lamps.

Advanced patented design featuring UVinaire® LED module. Highly configurable for easy product integration with continuous monitoring.



Full in-house optical, electrical, and mechanical design capabilities. ISO 9001:2015 certified manufacturing facility located in Kentucky, USA.

This PearlAqua Micro is Tested and Certified by NSF International against NSF/ANSI Standard 55 for materials and structural integrity requirements.



Component

FEATURES	
Mercury Free	Low Power Consumption
Remote Start/Stop	Unlimited On/Off Cycling
Instantaneous On	Thermal Monitoring
Consistent Performance Across Water Temperature Range	

OPTIONS
UV Intensity Monitoring (C Only)
LED Status Output
Power Cable Length and Connector
Mounting Bracket

SPECIFICATIONS						
<i>Specifications provided as a guide. Variations possible based on customer requirements.</i>						
Product Name		PearlAqua Micro				
Model Number		3B	6B	9C	12C	
Max Flow ¹ [lpm (gpm)]	UV Dose (mJ/cm ²)	10	1.2 (0.3)	2.0 (0.5)	5.3 (1.4)	8.0 (2.1)
		16	On Request			
		40				
Headloss at Max Flow [mbar (psi)]		65 (0.9)	165 (2.4)	407 (5.9)	917 (13)	
Inlet/Outlet Water Connection		Male: 3/8", 11mm, or other		Male: 3/8", 1/2", or other		
Weight [g (oz)]		77 (2.7)		162 (5.7)		
Max Operating Pressure ² [bar (psi)]		8.3 (120)				
Environmental Protection		IP68				
Lamp Life ³ [hours]		up to 10,000				
Max Ambient Temp [°C (°F)]		80 (176)				
Fluid Temperature [°C (°F)]		0-50 (32-122)		0-45 (32-113)		
Electrical Connection		4-Core Cable, 150 mm (6") length				
Input Voltage [V DC]		12 or 24		12		
Input Power ³ [W]		2.5 - 4	5 - 8	7 - 11	9 - 14	

NOTES
¹ 3rd party bioassay tested with T1 Phage and MS-2 Phage at 98% UV-T with reference to 254 nm. Not verified or tested by NSF International
² 3rd party tested at 2.4x greater, 19.8 bar (288 psi) at temperature 19 °C (67 °F)
³ Dependent on product configuration and application
Specifications subject to change

